



03.5850 - SCANGRIP ZONE 2 LED rechargeable headlamp providing up to 200 lumen

| | |
|----------------|-----------------------|
| Price with TAX | 173.99 zł |
| Price | 141.46 zł |
| Availability | Dostępny - 24h |
| Shipping time | 24 hours |
| Number | 03.5850 |
| Producer code | 03.5850 |
| EAN code | 5708997358504 |

Product description

RECHARGEABLE HEADLAMP WITH 200 LUMEN

The new ZONE 2 headlamp provides optimum work light illuminating the entire field of view. It is now delivering even more value for money for the professional user.

The light output was increased by 33 % from 150 to 200 lumen, and with improved battery technology and now three light settings, including the new »reading mode«, the maximum operating time was increased to 22 hours.

The design has become more compact, modern and user-friendly, and the new ZONE 2 also features a battery indicator and upgraded IP rating to IP54.

The upgraded ZONE 2 comes with 3-step function. The first step is reading mode providing 20 lumen, that is just enough light to read a manual.

Why you should choose ZONE 2?

- Lights up your entire field of view
- New reading mode setting
- 22 hours operating time
- Improved battery technology
- Compact and user-friendly design

Net Weight (kg)

0.08

Length (mm)

0.84

Width (mm)

31.50

Height (mm)

0.37

Gross weight, packaging (kg)

0.14

Length, packaging (mm)

104.00

Width, packaging (mm)

90.00

Height, packaging (mm)

41.00

Sales display included

No

Qty in outer box

24.00

Luminous Flux, Max (Lumen)

200

Luminous Flux, Min (Lumen)

20

Illuminance, Max (Lux@0,5m)

400

Illuminance, Min (Lux@0,5m)

40

LED performance (lm/w)

155

CCT (Kelvin)

6000

CRI

Ra > 80

Adjustable Light Output

3 steps

Beam Angle Main

120°/60°

Power source

Rechargeable Battery

Battery type

Li-Polymer

Battery capacity (mAh)

1200

Battery voltage (V)

3.70

Cable

1m USB charging cable

Charging voltage DC (V)

5.00

Charging current (A)

0.00

Charging input voltage (V)

100-240V AC 50/60Hz

Power Consumption (W)

2.50

Charger included

No

Operating time with max. lumen (hours)

2.00

Charging time (hours)

2.50

Ingress protection

IP54

Impact protection

IK07

Operating temperature (°C)

-10 °C to +40 °C

Impact resistance (meter)

1.00

Operating time with min. lumen (CAS/hours)

22